



Explosion-Proof Flexible Connecting Hose



Type	Explosion-Proof Hose
Order No.	Hose001
Specifications	G1/2 Outside-G3/4 Outside
Casing Material	Stainless steel, rubber
Protection Class	IP65
Temp.range min	-20℃
Temp.range max	+70℃
Operational Areas	outdoor
Mounting	Installed on the junction box
Applications	Can be used in hazardous areas; Zone 1and Zone 2. Can be used in explosive gas atmospheres ofCategory II All B and II C. Can be Used in dangerous places such as chemical industry, oil refining, petroleum exploitation, offshore oil platform, oil tanker, pharmaceutical industry, military industry, etc. , the utility model is used for connecting the inlet and outlet lines of explosion-proof electrical equipment or connecting the steel pipe wiring with greater bending difficulty or vibration.
Explosion-proof mark	ExdIIGb/DIP A28
Executive standard	GB3836.1、GB3836.2、GB12476.1、GB9600、IEC60079

Xi'an Kaidun Intelligent Technology Co.,Ltd
3rd Floor West of Building 101, Xirui Industrial Park, No. 569
Jincheng 3rd Road, Xi'an National Economic and Technological
Development Zone, Xi'an City,China . Code NO.: 710000
Email:enquiry@kaidunex.com
www.kaidunex.com

Other technical data on request / subject to change without notice